

Safeplast NA Company, Ltd.

14 W Cameron Road
Essex, Ontario, Canada N8M 2X5

www.safeplast.com

**Safe-Wrap
with hook and loop closure**

- **Fast and Easy Installation**
- **Post Assembly Installation**
- **Ideal for Retrofit to existing equipment**
- **Urethane coated 1050 Ballistics Nylon**
- **Lightweight, tough and highly flexible**
- **Low Co-efficiency resists wear**
- **Proprietary bonding process allows cutting without fraying**
- **Custom sizes available**



Bundle O.D.	Circumference	Sleeve Width Flat
1"	3.25"	4"
2"	6"	7.75"
3"	9.4"	11"
4"	12.5"	14"
5"	15.75"	17.25"
6"	18.8"	20.375"
7"	22"	23.5"
8"	25.125"	26.625"



Safeplast NA Company, Ltd.

14 W Cameron Road

Essex, Ontario, Canada N8M 2X5

www.safeplast.com

Safe-Wrap with hook and loop closure

Safe-Wrap Product Information

Constructed of 1050 Ballistic Nylon with a urethane coating, Safe-Wrap feature a special designed hook & loop closure. Safe-Wrap can be cut with scissors to any desired length.

Features

- **Fast field repair and replacement of damaged sleeves, no need to disconnect lines.**
- **Quick and Easy bundling of hose groups**
- **Eliminates contamination of hydraulic line during replacement.**
- **Protects machine operators from hose bursts.**
- **Use to re-route hoses away from potential hazards.**
- **Provides resistance to heat, UV and abrasion**
- **Enhances equipment appearance.**
- **Eliminates cable ties.**
- **Low coefficient of friction makes movement in tight spaces easier**
- **Multiple open and close cycles.**

Closure shear strength 22 lbs. per square inch

1500 cycles without degradation

1050 denier nylon type 66 sub-straight

Mil spec 1.5—1.75 oz urethane coating on application side

Heat bonded closure

Minimum temperature -65°F Maximum temperature +225°F

U.V. resistance